



Train car/wheel positioning

Wheel sensors DKU-02 Koldun, DKT, DKL ESSO-ILS Axle Counting System





R&D Company Promelectronica is an expert in the axle counting systems. Our axle counting systems ensure train traffic safety on all Railways of the JSC Russian Railways and actively used in Indonesia, Bulgaria, Brazil and other countries. We use the axle counting technology to solve various Customer's tasks. Our equipment is used in information and logistic systems to monitor rolling stock movement, identify types and numbers of the train cars, CTC, etc.

# RS-485 SERIAL DIGITAL INTERFACE DKU-02 KOLDUN WHEEL SENSOR

Detects wheel presence in the sensor area and passing of a wheel, performs axle counting considering the movement direction, calculates wheel movement parameters, performs self-diagnostics and transmission of received data to the upper-level system.

#### **AREAS OF APPLICATION**



Automatic coupling control systems



Warning of operating personnel about incoming trains



Rolling stock speed measurement



Train car weighing



Train car type identification



Positioning in hot box detection systems

## **ADVANTAGES**

- Software configurable to the Customer's requirements.
- Autonomous processing of received information.
- Direct connection to information and logistic systems.
- Extended operating temperature range: from -60 up to +70 °C.
- Increased reliability of operation when affected by special vehicles (snow-clearing vehicles, track carts, etc.).

## PARALLEL DIGITAL INTERFACE («CURRENT LOOP») DKT WHEEL SENSOR

Detects wheel presence within the sensing area, transmits signal on wheel presence and functionality check data to the upper-level system.

#### **AREAS OF APPLICATION**

- In automation systems of railway shunting stations.
- As a part of information and logistic systems and control and measurement systems.

## **ADVANTAGES**

- The sensor has two wheel sensing areas.
- Data transmission speed on presence of a wheel to evaluator device: up to 8 ms.
- Extended temperature range: from -60 up to +70°C
- Easy and fast installation on all rail types.
- Does not require routine maintenance.

**DKT Wheel Sensor** 

#### **POTENTIAL-FREE INTERFACE**

#### **DKL RAIL CONTACT SENSOR**

Detects train movement. Suitable for mobile solutions, lightweight and compact sensor.

#### **AREAS OF APPLICATION**

- Warning of track maintenance personnel about incoming trains.
- Pedestrian-crossing warning systems.
- Precise wheel positioning systems, etc.

#### **ADVANTAGES**

- Extended temperature range: from -60 up to +70 °C.
- Simple and quick installation on all rail types, installation time – less than 5 minutes.
- Does not require maintenance.

**DKL Wheel Sensor** 

## **ESSO-ILS AXLE COUNTING SYSTEM**

The system is used as a part of information and logistic systems to track locomotive and train car movement on the station.

упсп

упсп

#### **ADVANTAGES**

- High reliability of the system, counting error probability does not exceed 1,0-10<sup>-6</sup>.
- The system uses safe DKU-M wheel sensors without additional electronic equipment on the track. The sensors are connected by a pair-wire to a distance up to 5 km.
- Data is fed to the upper-level system via standard ModBus TCP protocol.
- The system provides power supply for the sensors, gathering of data and protection against lightning and surge overvoltages.
- Independent of trackside equipment, the indoor part of the system can be upgraded to ESSO-M or ESSO-M-2 system and connected to an interlocking system.
- The system does not require routine maintenance.

**ESSO-ILS Indoor equipment** 





npcprom.ru